

PURE

WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1 (when applicable / EN 13501)	Dfl-s1*
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value)	(BHN) EN1534	
Maple		4,8
Ash		4,0
Beech		3,8
Oak		3,7
Walnut		3,2
Birch		2,6
Taber Abraser/Lacquer's wear resistance Proteco Lacquer Proteco Natura Proteco Hardwax Oil <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	4000 3500 N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17
Thermal insulation value (RT m² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K) 13 mm 14 mm	EN 12664 / EN 14342:2013	0,104 0,11
Construction	3-layer with softwood core	
* Cfl-s1 for lacquered products can be provided on demand.		

INSTALLATION		
Installation method	2-lock for floating or glue down	
Installation instruction	Download from www.tarkett.com Contact your supplier for more details	
Underfloor heating compatible	Maximum floor surface temperature 27°C with self-regulating under-floor heat system *	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²		
* Not suitable for the woodspecies beech and maple.		

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Pure 14 mm Proteco Lacquer / Proteco Natura

97 %
97 %
Natural
Renewable

100 %
Recyclable

Pure 13 mm Proteco Lacquer, Proteco Natura / 14 mm Proteco Hardwax Oil

98 %
98 %
Natural
Renewable

100 %
Recyclable



2-LOCK



Tarkett

PURE

WOOD - PRODUCT DATASHEET 2021


DESIGN

The authentic design of Mother Nature is left untouched in this collection in order to preserve and enhance the unique character of each board and to create floors with an everlasting style.


PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Pure Birch TreS	8540002	2 281 x 194 x 14	3-strip	Protecto Lacquer	-	-	Lively	Warm beige	1	0020-0106	3,5	6	2,66	93,10	7,9
Pure Maple Nature TreS	8517003	2 281 x 194 x 14	3-strip	Protecto Lacquer	-	-	Calm	Warm beige	2	0020-0106	3,5	6	2,66	93,10	7,9
Pure Ash Nature TreS	7965005	2 281 x 194 x 14	3-strip	Protecto Lacquer	-	-	Lively	Warm beige	3	0020-0106	3,5	6	2,66	93,10	7,9
	7965008	2 281 x 194 x 14	3-strip	Protecto Natura	-	-	Lively	Warm beige	3	0020-0106	3,5	6	2,66	93,10	7,9
Pure Beech Nature TreS	7930003	2 281 x 194 x 14	3-strip	Protecto Lacquer	-	-	Calm	Warm beige	4	0020-0106	3,5	6	2,66	93,10	7,9
Pure Oak Select TreS	7870024	2 281 x 194 x 14	3-strip	Protecto Lacquer	-	-	Calm	Warm brown	5	0020-0106	3,5	6	2,66	93,10	7,9
Pure Oak Nature Plank XT	7877027	2 200 x 190 x 14	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0105	3,5	6	2,51	87,85	7,9
	7877028	2 000 x 190 x 14	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0105	3,5	6	2,28	79,80	7,9
Pure Oak Nature Plank	7876001	2 200 x 162 x 14	1-strip	Protecto Lacquer	-	Minibevel	Calm	Warm brown	5	0190-0105	3,5	6	2,14	77,04	7,9
	7876070	2 200 x 162 x 14	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0105	3,5	6	2,14	77,04	7,9
	7876069	2 000 x 162 x 14	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0105	3,5	6	1,94	69,84	7,9
	7878002	2 200 x 162 x 13	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0103	2,5	6	2,14	77,04	7,3
	7878001	2 000 x 162 x 13	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0103	2,5	6	1,94	69,84	7,3
Pure Oak Nature MidiPlank	41016004	1 850 x 134 x 13	1-strip	Protecto Natura	-	Minibevel	Calm	Warm brown	5	0190-0103	2,5	8	1,98	55,44	7,3
Pure Oak Nature MiniPlank	8720020	1 245 x 117 x 14	1-strip	Protecto Natura	Brushed	Minibevel	Calm	Warm brown	5	0190-0105	3,5	8	1,17	65,52	7,9
Pure Oak Nature DuoPlank	8727002	2 281 x 194 x 13	2-strip	Protecto Natura	-	-	Calm	Warm brown	5	0020-0104	2,5	6	2,66	106,4	7,3

Due to the nature of the material this table shows typical values.

1: Betula Pendula, 2: Acer Saccharum, 3: Fraxinus Angustifolia, 4: Fagus Sylvatica, 5: Quercus Robur & Quercus Petraea




Pure Birch TreS



Pure Maple
Nature TreS



Pure Ash
Nature TreS




Pure Beech
Nature TreS



Pure Oak
Select TreS



Pure Oak
Nature Plank XT



Pure Oak
Nature Plank



Pure Oak
Nature MidiPlank



Pure Oak
Nature MiniPlank



Pure Oak
Nature DuoPlank

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com

PURE

WOOD - PRODUCT DATASHEET 2021

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Pure Oak Nature TreS	7869015	2 281 x 194 x 14	3-strip	Proteco Lacquer	-	-	Calm	Warm brown	5	0020-0106	3,5	6	2,66	93,10	7,9
	8723001	2 281 x 194 x 13	3-strip	Proteco Lacquer	-	-	Calm	Warm brown	5	0020-0104	2,5	6	2,66	106,4	7,3
	7869017	2 281 x 194 x 14	3-strip	Proteco Natura	-	-	Calm	Warm brown	5	0020-0106	3,5	6	2,66	93,10	7,9
	8723004	2 281 x 194 x 13	3-strip	Proteco Natura	-	-	Calm	Warm brown	5	0020-0104	2,5	6	2,66	106,4	7,3
	7870038	2 281 x 194 x 14	3-strip	Proteco Hardwax Oil	-	-	Calm	Warm brown	5	0020-0106	3,5	6	2,66	93,10	7,9
Pure Oak Nature TreS (brushed)	7870061	2 281 x 194 x 14	3-strip	Proteco Natura	Brushed	-	Calm	Warm brown	5	0020-0106	3,5	6	2,66	93,10	7,9
Pure Oak Rustic Plank XT	7879004	2 200 x 190 x 13	1-strip	Proteco Natura	Brushed	Minibevel	Lively	Warm brown	5	0190-0103	2,5	6	2,51	87,85	7,3
	7879003	2 000 x 190 x 13	1-strip	Proteco Natura	Brushed	Minibevel	Lively	Warm brown	5	0190-0103	2,5	6	2,28	79,80	7,3
Pure Oak Rustic Plank	7876957	2 200 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Lively	Warm brown	5	0190-0105	3,5	6	2,14	77,04	7,9
	7876958	2 000 x 162 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Lively	Warm brown	5	0190-0105	3,5	6	1,94	69,84	7,9
	7876037	2 200 x 162 x 14	1-strip	Proteco Hardwax Oil	Brushed	Minibevel	Lively	Warm brown	5	0190-0105	3,5	6	2,14	77,04	7,9
	7876030	2 000 x 162 x 14	1-strip	Proteco Hardwax Oil	Brushed	Minibevel	Lively	Warm brown	5	0190-0105	3,5	6	1,94	69,84	7,9
Pure Oak Rustic MiniPlank	8720008	1 245 x 117 x 14	1-strip	Proteco Natura	Brushed	Minibevel	Lively	Warm brown	5	0190-0105	3,5	8	1,17	65,52	7,9
Pure Oak Rustic DuoPlank	8727003	2 281 x 194 x 13	2-strip	Proteco Natura	Brushed	-	Lively	Warm brown	5	0020-0104	2,5	6	2,66	106,4	7,3
Pure Oak Rustic TreS	8723020	2 281 x 194 x 13	3-strip	Proteco Lacquer	-	-	Lively	Warm brown	5	0190-0103	2,5	6	2,66	106,4	7,3
	8723021	2 281 x 194 x 13	3-strip	Proteco Natura	-	-	Lively	Warm brown	5	0190-0103	2,5	6	2,66	106,4	7,3
Pure Oak Antique Plank	7876018	2 200 x 162 x 14	1-strip	Proteco Natura	Brushed	Maxibevel	Lively	Warm brown	6	0190-0105	3,5	6	2,14	77,04	7,9
Pure Walnut TreS	8577007	2 281 x 194 x 14	3-strip	Proteco Lacquer	-	-	Expressive	Warm brown	7	0020-0106	3,5	6	2,66	93,10	7,9
	8577008	2 281 x 194 x 14	3-strip	Proteco Natura	-	-	Expressive	Warm brown	7	0020-0106	3,5	6	2,66	93,10	7,9

Due to the nature of the material this table shows typical values.

5: Quercus Robur & Quercus Petraea, 6: Quercus Alba, 7: Juglans Nigra



Pure Oak Nature TreS



Pure Oak Nature TreS (brushed)



Pure Oak Rustic Plank XT



Pure Oak Rustic Plank



Pure Oak Rustic MiniPlank



Pure Oak Rustic DuoPlank



Pure Oak Rustic TreS



Pure Oak Antique Plank



Pure Walnut TreS

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com

PURE SVANEN

WOOD - PRODUCT DATASHEET 2021

FOR AREAS WITH NORMAL TRAFFIC LIKE DOMESTIC ENVIRONMENT, HOTEL ROOMS AND SIMILAR.



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,11
Construction	3-layer with softwood core	

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
Tarkett wooden floors have a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Pure 14 mm Matt Lacquer



2-LOCK



3029 0022

Tarkett

PURE SVANEN

WOOD - PRODUCT DATASHEET 2021

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Pure Oak Nature TreS NS	7869047	2 281 x 194 x 14	3-strip	Matt Lacquer	-	-	Calm	Warm brown	1	0020-0106	3,5	6	2,66	93,10	7,9
Due to the nature of the material this table shows typical values.															

1: Quercus Robur & Quercus Petraea



The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com